



umano**medical**

## MEDICAL SURGICAL BED WITH SCALE AND BED EXIT DETECTION SYSTEM



10" / 25.4 cm low height with built-in bed exit detection system to minimize falls

Seamless design to maximize infection control

Easy to use and fully featured

## LOW HEIGHT • EASY TO CLEAN • EASY TO USE FULLY FEATURED



Seamless smooth surfaces maximizing infection control



Conveniently located USB power outlets to plug in mobile devices



Open architecture to simplify cleaning and mattress installation



Under bed clearance for lift and overbed table compatibility

## MEDICAL SURGICAL BED WITH SCALE AND BED EXIT DETECTION SYSTEM

### BED FEATURES

- 4 DC actuators
- Battery back-up
- 4 casters with central brake
- One hand release siderails
- Open architecture
- One step Trendelenburg
- One step vascular foot position
- Integrated pump holder
- Transport handles on headboard and footboard
- 4 corner roller bumpers
- Nurse controls integrated into siderails and footboard
- Patient controls integrated into siderails
- Patient control lockout
- Boostless™ Backrest System
- Backrest angle indicator
- Compliant with standard IEC 60601-2-52

### OPTIONAL FEATURES

- 10" / 25.4 cm low height
- Built-in-bed scale system
- Built-in bed exit detection system
  - 2 or 3 levels of sensitivity
- Remote bed exit alarm connectivity
- Bed exit side view lights
- Smart screen on footboard control
- Trendelenburg angle displayed on footboard
- Auto-contour
- Programmable lowest height
- Patient surface length (80" or 84")
- 3 position integrated bed extender :
  - 80" / 203.2 cm   84" / 213.4 cm   90" / 228.6 cm
- 5" / 12.7 cm single or dual casters (optional antistatic casters)
- 120-volt / 5 A or 220-volt / 2 A insulated outlets with USB mobile device power outlets
- Foot end back-up control on the frame
- CPR release handle
- Roller type wall protection bumpers
- Higher siderails (for 8" mattress)
- Foot control system
- Downward motion interrupt
- Communication port (for upgradable bed software)
- Nightlights
- One-touch button groups
  - 30-degree head of bed
  - One-button chair position
  - Flat bed position
  - Backlit patient controls
  - Room light control
  - Reading light control
  - Nurse call

### Accessories\*

- Patient helper system
- Upright oxygen bottle holder
- IV poles (permanent & removable)
- 6" or 10" / 15 or 25.4 cm Bed extender cushion

\* To see all accessories available, visit our website

### Specifications for model FL36 / ook-snow

|                                         |                               |
|-----------------------------------------|-------------------------------|
| Overall length (with bumpers)           | 88" / 224 cm                  |
| Extended length                         | 92" - 98" / 234 - 249 cm      |
| Overall width                           |                               |
| Siderails down                          | 39.25" / 100 cm               |
| Siderails up                            | 40.5" / 102.9 cm              |
| Weight capacity                         | 600 lb / 272 kg               |
| Height range (to litter top)            |                               |
| Low (with 5" / 12.7 cm dual casters)    | 10" / 25.4 cm                 |
| High (with 5" / 12.7 cm dual casters)   | 30" / 76.2 cm                 |
| Low (with 5" / 12.7 cm single casters)  | 11.5" / 29.2 cm               |
| High (with 5" / 12.7 cm single casters) | 31.5" / 80 cm                 |
| Patient surface positioning             |                               |
| Backrest                                | 0° to 60°                     |
| Knee Gatch                              | 0° to 30°                     |
| Trend. / Reverse Trend.                 | ± 16°                         |
| Boostless™                              | 4" / 10.2 cm                  |
| Patient surface dimensions              | 35" x 80" or 84"              |
|                                         | 88.9 x 203.2 or 213.4 cm      |
| Caster diameter                         | 5" / 12.7 cm                  |
| Bed weight                              | 375 to 438 lb / 170 to 199 kg |

### Electronics

|                                              |                                                                         |
|----------------------------------------------|-------------------------------------------------------------------------|
| Compliant with standard                      | IEC 60601-1 3 <sup>rd</sup> edition                                     |
| Volts                                        | 120 V AC / 220-240 V AC                                                 |
| Ampere rating                                | 4.25 A (9.25 A with 120 V outlets) / 2.15 A (4.15 A with 220 V outlets) |
| Current leakage                              | < 300 micro amps                                                        |
| Frequency                                    | 60 Hz / 50 Hz                                                           |
| Hospital grade plug                          | Yes                                                                     |
| Battery type                                 | Sealed rechargeable lead acid 1.2 Ah, 2 * 12 V                          |
| Scale system accuracy (in all bed positions) | 0.5% with a maximum difference of 1.1 lb / 0.5 kg                       |

*Umano Medical* reserves the right to change specifications without notice.



### Umano Medical Inc.

230, boul. Nilus-Leclerc, L'Islet QC G0R 2C0 CANADA  
 Toll free number : 1 844 409-4030  
 information@umanomedical.com  
 umanomedical.com